

# AUTO BAG R1075 AUTOMATIC BAGGER



## Product Description

Performance package—air expeller, bag support, and flat seal assist!

The Auto Bag R1075 is an automatic tabletop sealing machine designed for a swift and efficient operation. This bagger is equipped with three options: Articulating Bag Support, Flat Seal Assist, and an Air Expeller.

Works with a wide variety of bags

The Auto Bag R1075 Automatic Bagger combines a powerful electric drive motor with pneumatic force during the packaging process. The flexible R1075 bagger works with Auto Bag brand pre-opened bags on a roll, ranging in size from 2" x 3" to 10" x 20". Poly bags can either be produced individually or in sets for kit packaging.

User-friendly controls

The unique, locking turntable links feature to provide ergonomic handling and bag changeover. Poly bags are automatically indexed, loaded by hand, then sealed using the automated sealer function, a standard footswitch, or via automatic cycle control. Programming the auto bagger is simple with a sequential interface. It can store ten job profiles, enabling a quick changeover of products. With low maintenance needed, quality parts and technical support, production time is amplified using the Auto Bag R1075 Automatic Bagger.

Safety

Safety highlights on this automatic bagger include:

- Low-pressure jaw closure.
- Jaw obstruction detection.
- Unobtrusive guards.

## Industries Served

- Electronics
- Healthcare
- Logistics
- Automotive
- Cosmetics
- Shipping



**STREAM PEAK INTERNATIONAL PTE LTD**  
Tel: +65 6610 7921 | Fax: +65 6862 2520  
Email: [enquiry@streampeak.com.sg](mailto:enquiry@streampeak.com.sg)

*Valuing Relationships, Protecting Goods*  
Address: 26 Tuas South Street 3, S(638026)  
Website: [www.streampeak.com.sg](http://www.streampeak.com.sg)

## Machine Features

- Capable of storing the sealing parameters for 10 jobs with on-board memory
- Automatically indexes the bag and positions it for fast loading and sealing
- Fastest bag changing capability in the industry
- Programmable time delay for operator pace control or integration with automatic feeding device
- Foot pedal, control panel, or optional photo-eye available to trigger bagger
- Strip Packaging

## Maintenance Benefits

- Off the shelf modular components for easy replacement
- Self-diagnostics ensure quick problem solving
- Designed to minimize preventative maintenance costs

## Safety Features

- Low-pressure closing with obstruction detection system for improved operator safety
- Unobtrusive guards
- Prominent emergency stop button
- 220 Volt version designed to meet CE requirements

## Sealing Features

### Air Expeller / Bag Deflator

Performance package, this feature mounts to the pressure bar and compresses the air out of the bag as it travels inward toward the machine just prior to the sealing process.

### Articulating Bag Support

Performance package, a pneumatically operated shelf that is used to support the bottom and back of the bag during the loading process. The shelf then tips down and out of the way after the bag has been sealed.

### Bag Spreader / Seal Flatteners

Performance package, opposing fingers that pull each side of the bag taught above the seal area to flatten the bag seal area; thus, decreasing the possibility of wrinkles in the seal area and increasing seal integrity.



## Options

### Adjustable Funnel with Preparation Table / Work Sorting Table

Stainless Steel table mounted above the machine that allows for sorting, storing and kitting of product before manually pushing the product into the adjustable funnel which guides the product into the bag.

### Additional Parts Funnels

Wide variety of standard and custom funnels to assist product handling

### Tabletop Console Stand

Mechanically adjustable stand for all the tabletop machines

## Product Specifications

Technical Specifications	
Speed	Up to 30 bags per minute (dry cycle)
Bag Width	2" - 10" (51mm - 254mm)
Bag Length	3" - 20" (76mm - 508mm)
Bag Thickness	1mil - 5mil
Seal Width	1/8"
Electrical Requirement	120v, 5a, 50/60hz
Air Requirement	80psi @ 2 - 5cfm (5.5bar @ 140 l/m)
Dimensions	26"W x 28"D x 22"H (661mm x 711mm x 559mm)
Weight	75lbs (35kg)
Warranty	1 year limited warranty, extendable to 5 years when exclusively using Rollbag brand bags on a roll
Origin	Made in the USA

## Related Products



Auto bag R785  
Automatic Bagger



Auto bag R1275  
Automatic Bagger



Auto bag Magnum HS  
Med Automatic Bagger



Auto bag R3200  
Automatic Bagger

